

AWC[®] C-232

Reverse Osmosis Membrane Cleaning Compound

ADVANTAGES

- Concentrated liquid formulation designed for use as a low pH cleaner of polyamide thin film composite membrane surfaces
- Designed for removal of tough organic scales such as calcium phosphonate, calcium polyacrylate, and calcium citrate
- Removes inorganic carbonate, phosphate, and hydroxide scales
- Effective even in cases of severe scaling - complete removal of scale reduces cleaning frequency
- Certified by NSF to NSF/ANSI Standard 60

TYPICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Odor	Characteristic
Solubility in water	Complete
pH (as is) @ 25°C	< 1
Specific Gravity	1.35 ± 0.05

PACKAGING

5 gallon pails, 55 gallon non-returnable plastic drums and 275 gallon totes

SAFETY & HANDLING

Store in cool, dry and well ventilated area. Keep containers closed. Wash contaminated clothes before re-use. Wash thoroughly after handling. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

The cleaning solution should be prepared using potable water that is free of residual chlorine or other oxidizing agents. Add 2 gallons of AWC C-232 to every 100 gallons of water (2% solution). Adjust the pH in the range 2–3. Recirculate the cleaning solution throughout the system, after redirecting the first 20% of the solution to drain. Do not exceed pressures, temperatures, and flow rates recommended by the membrane manufacturer. Cleaning efficacy can be further improved by heating the cleaning solution and alternately circulating the solution for 15 minutes and then soaking the membranes for 15 minutes. Repeat as necessary. Monitor the pH range periodically throughout the cleaning. When pH increases above the desired range, it should be adjusted by adding more AWC C-232.

